

# SF-T943A-5P4N1

Safire PRO Turret Camera

Output 4in1

5 MP high performance CMOS

2.8 mm Lens | 40 m IR range

Audio over Coaxial cable

Weatherproof IP67



Safire

Turret HDTVI, HDCVI, AHD and Analog Camera

PRO Range

High Performance CMOS

HD 5Mpx (2560x1944)

Output 4in1

2.8 mm Lens

0 Lux

IR Matrix Range 40 m

Audio over Coaxial

3D DNR

IR Cut

Weatherproof IP67

# Specifications

Brand	Safire
Range	PRO
Image sensor	High Performance CMOS
Maximum resolution	5 Mpx (2560x1944)
Resolution	5Mpx to 20 fps,4Mpx to <30 fps, 1080P to 25 fps
Lens	2.8 mm
Minimum illumination	0.01 Lux @(F1.2, AGC ON)
Infrared lighting	0 Lux / SMART IR (40 m)
Day / Night	Auto / Colour / BW (Black and White)
Audio	Built-in microphone (Audio via coaxial cable)
Video output	1 x BNC switchable between HDTV / HDCVI / AHD / CVBS
Video output switching	Via Switch
Basic functions	OSD menu (remote)
Configurable OSD functions	DWDR, 3D-DNR, AWB, ATW, BLC, AGC, Mirror, Smart IR
Lens Adjustment	3 Axis
Power	DC 12 V / 324 mA, 3.7 W max
Degree of protection	Weatherproof IP67
Temp. operation	-40° C ~ +60° C
Material	Metallic
Dimensions	91 (H) x 109 (Ø) mm
Base diameter	85 (Ø) mm / 3 screws
Weight	325 g